

Feature Packed. Rugged Functionality. Made in Spain.



TANK

4 Gallon Capacity w/ Internal Anti-Slosh Baffling, Bottom Drain, and Pump Filter

PUMP & CONTROL UNIT

Speeds: 3 Speeds, Zero Drop-off

Pressure: 34 - 102 psi

Flow Rate: 0.39 - 0.7 gpm

Diaphragm: Santoprene

HANDLE & LANCE

Handle: Polypropylene & Brass

Lance: 16.75" Stainless Steel

HOSE

47.25" Polyester Mesh
Reinforced PVC

SPECIFICATIONS

Dimensions: 16.5" x 10" x 22"

Temperature: 32°F - 122°F

Battery Life: Up to 3 hrs

Weight: 9 lb

INCLUDES

3 Nozzles: Adjustable, 0°, 25°
18v, 2600 mAh Battery
Battery Charger



Now available from Ensystex, the **PULMIC INDUSTRIAL 15** is a true professional workhorse. Weighing just 9 lbs, the fully injection-molded tank has no drilled holes, eliminating vulnerable leak points, while an internal anti-slosh baffle maximizes balance on the move.

The 3S Electronic Spraying System delivers up to 100 PSI of consistent pressure throughout the charge. Maintenance is simple with an isolated side battery compartment and an easy-access service panel. Best of all, migrating your fleet is seamless and cost-effective thanks to a cross compatible battery ecosystem.

Full Brochure



Features Video

